



Bulk Digital Cable

Digital Audio

Direct Box/Interface

Audio Cables

Connectors



Video

Bulk Cable

Cable Management

Custom Shop

75 Ohm S/P-DIF Coax




Mogami 2964 S/P-DIF cable is a compact 75 ohm coaxial cable suited for digital interfacing. Features compact, yet flexible construction, with precision extruded copper to eliminate data loss due to reflections. An ideal cable for rack and interconnect wiring.

Mogami S/P-DIF cable

Order #	Model	Cond	Shield	Gauge	OD (in)
W170 2964-xx	W2964-00	1	Served	24 AWG	.189

Roll Lengths: 656' / 200m
Colours: Blk-00, Red-02, Yel-04, Grn-05, Blu-06

110 Ohm AES/EBU




Mogami 3080 AES/EBU cable is developed specifically for the 110 ohm standard for two-channel data transmission. This robust cable is constructed using extremely tight extrusion tolerances resulting in < +/- 5% deviation from 110 ohms which reduces reflections to a minimum. Features super-flexible jacket, pre-tinned drain and served shield. Use **Mogami W3173** for longer runs.

Mogami AES/EBU cable

Order #	Model	Cond	Shield	Gauge	OD (in)
W500 3080-xx	W3080	2	Served	24 AWG	.197
W550 3173-00	W3173	2	Served	18 AWG	.307

Roll Lengths: 3080 - 164' / 50m, 328' / 100m, 656' / 200m, 3173 - 983' / 300m
Colours: 3080 - Blk-00, Blu-06, 3173 - Blk-00




Mogami 3159 rack and console cable is a compact 110 ohm AES/EBU cable designed for internal console and patch bay wiring where small size and flexibility are considerations. Flexible PVC jacket, pre-tinned drain wire, and served shield are key features.

Mogami 110-ohm AES/EBU cable

Order #	Model	Cond	Strands	Gauge	OD (in)
W500 3159-xx	W3159	2	7x32	24 AWG	.126

Roll Lengths: 328' 100m, 656' / 200m
Colours: Blk-00, Gry-08




Mogami 3160-3163 snake cable is a super-flexible, easy to work with, 110 ohm multi-channel cable. Modelled after the world standard Mogami EZ-ID audio multipair, W3160-3163 uses **Mogami W3159** internally (see above). Flexible PVC jacket, pre-tinned drain wire, served shield for each pair.

Mogami 110-ohm multi-channel cable

Order #	Model	Cond	Strands	Gauge	OD (in)
W500 3160	W3160	2pr	7x32	24 AWG	.354
W500 3161	W3161	4pr	7x32	24 AWG	.413
W500 3162	W3162	8pr	7x32	24 AWG	.543
W500 3163	W3163	12pr	7x32	24 AWG	.669

Roll Lengths (ft): 328 / 500
Colours: Blk-00

T-DIF Twisted Pair



Mogami 2845 T-DIF shielded twisted pair cable is made with 110 ohm copper conductors for optimal transmission of T-DIF (Tascam Digital Interface) signals. Precision extruded oxygen free copper cores reduce data loss due to reflection.



Mogami T-DIF cable

Order #	Model	Cond	Strands	Gauge	OD (in)
W500 2845-08	W2845	13pr	7x37	28 AWG	.394

Roll Lengths: 500' / 152m
Colours: Gry-08



MIDI Synchro



- Compact overall size
- OFC core conductors
- Twisted pair
- Braided copper shield
- Super-flex PVC jacket


Mogami 2948 MIDI cable for use in applications where high performance is required such as MIDI sample dump and MTC time code transmission. Features two pairs, one of which is twisted, which reduces errors caused by electromagnetic noise induction. Super-flexible jacket, ideal for long distances without delay or data errors caused by reflection.

Mogami MIDI cable

Order #	Model	Cond	Strand	Gauge	OD(in)
W530 2948	W2948	2pr	30x40	26 AWG	.197

Roll Lengths: 328' / 100m, 656' / 200m
Colours: Blk-00

RS-422 Balanced Voltage Interface



- Conductors 1 & 2
- Twisted pairs (2)
- Served copper shield
- PVC outer jacket
- Conductors 3 & 4

Mogami 2997 RS-422 'balanced voltage' is a small and flexible cable designed to fit most D-sub 9-pin connectors as used in RS-422 applications. EZ-ID numbered print system on cores for easy identification. Simple PVC jacket, balanced twisted pair with served shield made with Mogami multiple strand oxygen free copper for reduced transmission error.


Mogami RS-422 cable

Order #	Model	Cond	Shield	Gauge	OD(in)
W650 2997	W2997	2pr*	served	25 AWG	.276

Notes: *balanced pairs + 4 separate signal conductors.

Roll Lengths: 500' / 152m, 1000' / 305m
Colours: Blk-00

VESA VGA



- PVC outer jacket
- Coax cable x 5
- Twisted pair x 3
- Power conductor
- Braided shield

Mogami 3206 video monitor cable is specifically designed to meet the VESA standard for plug and play displays. All the signal conductors necessary are present for a compliant host device to power and communicate set-up data with a VESA standard monitor over long runs.


Mogami VESA VGA cable

Order #	Model	Cond	Shield	Gauge	OD(in)
W600 3206-08	W3206	17	braided	28 AWG	.386

Notes: 5 x 75ohm 28AWG coax conductors + 3 x 28AWG twisted pairs + 1 x 28AWG power conductor.

Roll Lengths: 250' / 76m, 500' / 152m
Colours: Gry-08

IEEE 1394 FireWire



- PVC outer jacket
- Power conductor
- Twisted pair x 2
- Power conductor
- Braided copper shield

Mogami 3208 1394 'FireWire' computer cable was designed for current and future high speed digital serial bus transmission such as the IEEE-1394 standard used today in audio/video interfacing. Use for all high speed real-time data transmission of sound, video and animation data. Features low attenuation, low cable skew and high propagation velocity.


Mogami 1394 FireWire cable

Order #	Model	Cond	Shield	Gauge	OD(in)
W550 3208-08	W3208	2 x 2pr	notes*	28 AWG	.240

Notes*: bal pairs (signal) each with insulator tape + braided shield + overall tape shield + 2 x Power conductors

Roll Lengths: 250' / 76m, 500' / 152m
Colours: Gry-08

Parallel Video / SCSI II



- Ultra flexible
- Twisted pairs x 11
- OFC core
- System ground
- Braided copper shield
- PVC outer jacket

Mogami 3037 digital video and SCSI II very high-speed interface cable with 11 twisted pairs that have been optimized to allow long distances through phase matching. Exceptionally low reflection, ideal for digital video interconnect.

Mogami digital video / SCSI cable

Order #	Model	Cond	Shield	Gauge	OD(in)
W550 3037	W3037	11pr	braided	24 AWG	.413

Notes: 11 twisted pairs + 2 system ground conductors.

Roll Lengths: 250' / 76m, 500' / 152m
Colours: Blk-00