



## Twisted Pair

Direct Box/Interface

Audio Cables

Connectors


Video

Bulk Cable

Cable/Management

Custom Shop

### Bulk Cable > Twisted Pair




**Radial RM-201 live balanced mic cable** features a twisted-pair construction with 24AWG conductors and served copper shield in matte PVC jacket. Cotton fillers for added durability and flex life make it ideal for stage, touring and other demanding professional applications.

### Radial cable

Order #	Model	Cond	Shield	Gauge	OD (in)
<b>B250 0200</b>	RM-201	2	served	24 AWG	.236

Capacitance: 21pF/ft (69pF/m)  
 Roll Lengths: 1000' / 305m  
 Colours: Blk-00, Red-02, Blu-06




**Mogami 2582 studio balanced low capacitance mic cable** with served shield is ideal for use in a recording environment. Features superflexible PVC jacket, 100% oxygen free copper conductors and high temperature cross-linked cellular polyethylene insulation. **Mogami 2552** is a low profile version of the same cable that is suited for break-outs and patch cords.

### Mogami cable

Order #	Model	Cond	Shield	Gauge	OD (in)
<b>W250 2582</b>	W2582	2	served	26 AWG	.236
<b>W250 2552</b>	W2552	2	served	26 AWG	.197

Capacitance: W2582, W2552: 27pF/ft (90pF/m)  
 Roll Lengths: 328' / 100m, 656' / 200m  
 Colours: Blk-00




**Mogami W2792 ultra-low noise low capacitance mic cable** is ideally suited for studio, stage, and broadcast applications where flexibility and low handling noise is required. Features additional conductive PVC shield, XLP insulators and precision extruded 100% oxygen free copper.

### Mogami cable

Order #	Model	Cond	Shield	Gauge	OD (in)
<b>W250 2792-xx</b>	W2792	2	served	26AWG	.236

'xx' = colour suffix; add suffix to end of order #.  
 Capacitance: 38.7pF/ft (127pF/m)  
 Roll Lengths: 328' / 100m, 656' / 200m  
 Colours: Blk-00, Red-02, Yel-04, Grn-05, Blu-06




**Mogami W2549 Neglex cable** is exceptional in detail and dynamic range. Developed at the world renowned Neglex research facility, this ultra-low capacitance cable incorporates proprietary symmetrical fillers for precise noise cancelling. 100% oxygen free copper is used throughout for optimal transmission and noise rejection. **W3106** is the stereo version of this cable, used for precise stereo imaging.

### Mogami cable

Order #	Model	Cond	Shield	Gauge	OD (in)
<b>W250 2549</b>	W2549	2	served	22 AWG	.236
<b>W250 3106</b>	W3106	2x2	served	24 AWG	.189x2

Capacitance: W2549, W3106: 3.4pF/ft (11pF/m)  
 Roll Lengths: 328' / 100m, 656' / 200m  
 Colours: Blk-00



**Mogami 2791 broadcast cable** is the ultimate in rugged flexibility and low capacitance. Features Neglex 100% oxygen free copper outer braid with cotton placement fillers that allow 164,000 bend cycles before break-down. 'XLP' Cross-linked polyethylene insulation and pure copper conductors provide very low capacitance for long cable runs.

### Mogami cable

Order #	Model	Cond	Shield	Gauge	OD (in)
<b>W250 2791-xx</b>	W2791	2	served	24 AWG	.217

'xx' = colour suffix; add suffix to end of order #.  
 Capacitance: 3.1pF/ft (10pF/m)  
 Roll Lengths: 328' / 100m, 656' / 200m  
 Colours: Blk-00, Red-02, Yel-04, Grn-05, Blu-06



# Bulk Mic Cable

Direct Box/Interface

Audio Cables

Connectors

Video


Bulk Cable

Cable Management

Custom Shop

## Quad

### Quad Mic Cable




**Radial RM204 broadcast quad cable** features dual twisted pair construction for added rejection of electromagnetically induced hum. Features braided shield and heavy duty matte PVC jacket. Ideal for broadcast and other applications where AC, lighting ballasts, and dimmers are potential problems.

### Radial quad audio cable

Order #	Model	Cond	Shield	Gauge	OD(in)
<b>B250 0400-xx</b>	RM-204	4	Braided	24 AWG	.242

'xx' = colour suffix; add suffix to end of order #.

Capacitance: 46pF/ft (151pF/m)  
 Roll Lengths: 500' / 152m, 1000' / 305m  
 Colours: Blk-00, Red-02, Blu-06





**Mogami 2893 quad patch cable** offers the ideal balance in size, tensile strength, flexibility and low capacitance for patch cords, splays and specialty applications. Precision extruded oxygen free copper, cotton fillers, superflexible PVC jacket and cross-link poly insulators for zero shrink back.

### Mogami quad audio cable

Order #	Model	Cond	Strand	Gauge	OD(in)
<b>W250 2893-xx</b>	W2893	4	served	26 AWG	.189

'xx' = colour suffix; add suffix to end of order #.

Capacitance: 3.4pF/ft (11pF/m)  
 Roll Length: 328' / 100m, 656' / 200m  
 Colours: Blk-00, Red-02, Yel-04, Grn-05, Blu-06



**Mogami 2534 Neglex quad cable** features a patented central filler for noise cancelling by symmetrical placement of dual twisted pair. Provides improved rejection of electromagnetic induction while lowering capacitance by 50% below industry norms. 100% oxygen free copper shield and conductors.

### Mogami quad audio cable


Order #	Model	Cond	Strand	Gauge	OD(in)
<b>W250 2534-xx</b>	W2534	4	served	24 AWG	.236

'xx' = colour suffix; add suffix to end of order #.

Capacitance: 4pF/ft (13pF/m)  
 Roll Lengths: 328' / 100m, 656' / 200m  
 Colours: Blk-00, Red-02, Yel-04, Grn-05, Blu-06

## Lavalier

### Lavalier Mic Cable



**Mogami 2697 & 3031 lavalier mic cables** are extremely flexible and small; ideally suited as new or replacement cables for lavalier and wireless mic systems. Made with the most supple PVC jacketing. These balanced, twisted pair cables have a served (W2697) or braided (W3031) shield and are made entirely of 100% oxygen free copper.


### Mogami lavalier mic cable

Order #	Model	Cond	Shield	Gauge	OD(in)
<b>W250 2697</b>	W2697	2	served	28 AWG	.098
<b>W250 3031</b>	W3031	2	braided	28 AWG	.110

Capacitance: 2697: 17pF/ft (57pF/m), 3031: 21pF/ft (70pF/m)  
 Roll Lengths: 328' / 100m, 656' / 200m  
 Colours: Blk-00

## Tube

### Tube Mic Cable



**Mogami 3172 tube mic cable** was designed specifically to complement and bring out the best of Microtech-Geffel and Neumann tube condenser microphones. This cable emulates the original factory Neumann cable but with even better noise and RF rejection; Unlike the original, a balanced twisted pair with dual served shields is provided for the audio signal. Features a super-flexible jacket and Neglex 100% oxygen free copper.

### Mogami tube mic cable

Order #	Model	Cond	Shield	Gauge	OD(in)
<b>W250 3172</b>	W3172	6	2xSrvd	26 AWG	.256

Capacitance: 17pF/ft (56pF/m)  
 Roll Length: 328' / 100m  
 Colours: Blk-00