



Bulk Video Cable

75 Ohm Coax

Direct Box/Interface

Audio Cables

Connectors


Video

Bulk Cable

Cable Management

Custom Shop

75 Ohm Coax




Mogami 2964 75 ohm video patch cable is a stranded core coaxial suited for both audio and video applications, such as studio interfacing. Small diameter and flexible design, suited for rack and interconnect wiring in all Hi-Z systems. Also available in dual configuration (W2965). Suggested BNC connector: C690 0004

Mogami 75 ohm coax cable

Order #	Model	Cond	Shield	Gauge	OD (in)
W170 2964-xx	W2964	1	Served	24 AWG	.189

'xx' = colour suffix, add suffix to order #.

Attenuation: .019 dB/ft (.061dB/m) @ 10 MHz
 Roll Lengths: 656' / 200m
 Colours: Blk-00, Red-02, Yel-04, Grn-05, Blu-06




Radial RV-59A and RV59F 75 ohm precision solid core video cables feature a double braided shield equivalent to Belden 8281. 20AWG solid center conductor for excellent signal transmission. Discreet black outer jacket. RV59F stranded is same as RV59 but with blue jacket and C/UL listed for permanent installations. Suggested BNC connector: C690 0007

Radial solid core precision 75-ohm coax cable

Order #	Model	Cond	Shield	Gauge	OD (in)
B650 5900-00	RV-59A	1	98%	20 AWG	.313
B650 5900-01	RV-59F	1	98%	20 AWG	.313

Attenuation: .012 dB/ft @ 20 MHz:
 Roll Lengths: 500' / 152m, 1000' / 305m
 Colours: Blk-00, Blu-01




Radial RV-59B 75 ohm precision stranded core video cable is a flexible double shielded RG-59 similar to the Belden 8281 coax but features a 21AWG stranded core for added flexibility. Ideal for long distance runs. Black outer jacket. Suggested BNC connector: C690 0003

Radial stranded core precision 75-ohm coax cable

Order #	Model	Cond	Shield	Gauge	OD (in)
B650 5901	RV-59B	1	98%	21 AWG	.313

Attenuation: .012 dB/ft @ 20 MHz
 Roll Lengths: 500' / 152m, 1000' / 305m
 Colours: Blk-00




Radial RV-59C 75 ohm solid core video cable is an RG-59 equivalent to Belden 8241 that features a 23AWG solid core for ease of assembly and PVC matte jacket for superior flexibility. Smaller OD jacket makes RV-59C ideal for patch cables. Suggested BNC connector: C690 0001

Radial superflex solid core coax cable

Order #	Model	Cond	Shield	Gauge	OD (in)
B650 5903	RV-59C	1	95%	23 AWG	.250

Attenuation: .018 dB/ft @ 20 MHz
 Roll Lengths: 500' / 152m, 1000' / 305m
 Colours: Blk-00



Radial RV-59D 75 ohm video cable is similar to Belden 8241 and features a 23AWG stranded core for increased flexibility. Smaller OD jacket makes RV-59D ideal for shorter patch cables. Suggested BNC connector: C690 0001

Radial superflex stranded core coax cable

Order #	Model	Cond	Shield	Gauge	OD (in)
B650 5904	RV-59D	1	95%	23 AWG	.250

Attenuation: .018 dB/ft @ 20 MHz
 Roll Lengths: 500' / 152m, 1000' / 305m
 Colours: Blk-00



RG-6
SVHS/Y-C
RGB

Direct Box/Interface

Audio Cables

Connectors


Video

Bulk Cable

Cable Management

Custom Shop

75 Ohm RG-6



Radial RG-6 75 ohm solid core video cable features 18AWG solid core conductor that makes it ideal for long cable runs and permanent installs. Combination braid plus 100% bonded foil shield for excellent RF rejection. FT-4 rated PVC outer jacket. Suggested BNC connector: C690 0007


Radial RGB cable

Order #	Model	Cond	Shield	Gauge	OD (in)
B650 6000	RG6	1	Dual*	18 AWG	.275

Attenuation: .021 dB/ft @ 100 MHz
 Roll Lengths: 1000' / 305m
 Colours: Blk-00

*Bonded foil shield over braided tinned copper shield.

SVHS / Y-C




Mogami 2947 SVHS parallel dual coax cable with precise 75 ohm construction to reduce phase shift. Allows 100 foot runs. Features compact and extremely flexible construction, precise oxygen free copper extrusion to reduce reflection and cross-linked cellular polyethylene insulators for low capacitance. Suggested SVHS connectors: C690 0204 (panel), C690 0203 (in-line Female), C690 0201 (in-line Male).

Mogami SVHS / y-c cable

Order #	Model	Cond	Shield	Gauge	OD (in)
W650 2947	W2947-00	2	Served	27 AWG	.118

Attenuation: .019 dB/ft (.061dB/m) @ 10 MHz
 Roll Lengths: 500' / 152m, 1000' / 305m
 Colour: Blk-00

Multi-Conductor RGB




Radial RV-501 RGB compact multi-channel coax is a high performance 75 ohm video cable that is offered in 5 conductor format. Features combination braid plus foil shield for maximum noise rejection. Black outer jacket with colour coded internal conductors. Suggested BNC connector: C690 0002

Radial RGB cable

Order #	Model	Cond	Shield	Gauge	OD (in)
B600 0500	RV501	5	Dual	20 AWG	.344

Attenuation: .068 dB/ft @ 100 MHz
 Roll Lengths: 250' / 76m, 500' / 152m, 1000' / 305m
 Colours: Blk-00




Mogami 3145 RGB 5 conductor cable for HD TV and RGB video is a high resolution cable ideal for short-run monitor applications where flexibility and ultra-compact size are important. Small enough to fit 15-pin Dsub connectors. Five colour coded conductors (RGB + H + V) in a super-flexible black PVC jacket. Suggested BNC connector: C690 0005.

Mogami RGB cable

Order #	Model	Cond	Shield	Gauge	OD (in)
W600 3145	W3145	5	Served	25 AWG	.386

Attenuation: .018 dB/ft @ 10 MHz
 Roll Lengths: 250' / 76m, 500' / 152m
 Colours: Blk-00



Mogami 3158 RGB 5 conductor video cable is ideal for monitor applications where high signal transmission over longer runs is desired. Features five colour coded conductors each with served shield in a super-flexible black PVC jacket. Suggested BNC connector: C690 0004

Mogami RGB cable

Order #	Model	Cond	Shield	Gauge	OD (in)
W600 3158	W3158	5	Served	25 AWG	.689

Attenuation: .015 dB/ft @ 10 MHz
 Roll Lengths: 328' / 100m, 656' / 200m
 Colours: Blk-00